

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
21 April 2005 (21.04.2005)

PCT

(10) International Publication Number
WO 2005/035642 A1

(51) International Patent Classification⁷: C08K 3/20,
3/22, 3/34, 3/36, 3/30, 3/14

(21) International Application Number:
PCT/AU2003/001336

(22) International Filing Date: 10 October 2003 (10.10.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): COM-
MONWEALTH SCIENTIFIC AND INDUSTRIAL
RESEARCH ORGANISATION [AU/AU]; Limestone
Avenue, Campbell, Australian Capital Territory 2612
(AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BELL, Daniel
[AU/AU]; 117 The Boulevard, Thomastown, Victoria 3074
(AU). CASEY, Phil [AU/AU]; 24A Britten Street, Glen

Iris, Victoria 3146 (AU). GOZUKARA, Yesim [AU/AU];
2 Brownlee Crescent, Wheelers Hill, Victoria 3150 (AU).
HILL, Anita [AU/AU]; 45 Manningtree Road, Hawthorn,
Victoria 3122 (AU). MARDEL, James [AU/AU]; 59
Leila Road, Ormond, Victoria 3204 (AU). MARKLEY,
Tracey [AU/AU]; 11 Amy Street, Camberwell, Victoria
3124 (AU). MEAKIN, Pavia [AU/AU]; 1 Pychley Drive,
Croydon, Victoria 3136 (AU). OH, Chull, Hee [AU/AU];
17 Bowman Street, Mt. Waverley, Victoria 3149 (AU).
TURNERY, Terry [AU/AU]; 11 Sherbrooke Road, Sher-
brooke, Victoria 3789 (AU).


(74) Agent: FREEHILLS CARTER SMITH BEADLE;
Level 43, 101 Collins Street, Melbourne, Victoria 3000
(AU).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE,
GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,


[Continued on next page]

(54) Title: WEAR RESISTANT POLYMERS

(a) × 1.0K



(b) × 6.0K



SEM micrograph of the surface of polyurethane containing 6.1wt%
alumina prepared via the solvent method.

(57) Abstract: A method of improving the wear resistance of
a polymer is disclosed comprising the steps of evenly dispers-
ing an ultrafine inorganic particulate material in the polymer at a
loading rate of 0.01 to 20wt% of the total weight of the particu-
late polymer composite. The mixing or dispersing is preferably
carried out under sub-atmospheric pressure conditions to ensure
little or no bubbles form in the mixture prior to curing.

Best Available Copy

WO 2005/035642 A1

WO 2005/035642 A1

KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

SE, SI, SK, TR). OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Best Available Copy